

# SMF2

16 mm, recessed, high profile, can be fully customized in accordance with any design solution, especially those with a focus on health & hygiene, weatherproof & anti-vandal, and more.

SMF2 is a fully customizable non-illuminated touch metal piezo switch, developed without moving mechanical elements to increase its durability and reliable service in the toughest conditions.

## Key Characteristics:

- Aviation Grade Aluminum or Stainless Steel 303 standard (304, 316 optional)
- Anodized Aluminum in silver, black, red, green, blue or gold finishes
- Laser Engraving or Anodized printing optional



## Electrical Data

---

Switch Function	N.O. Momentary 125-300msec (N.C. optional). Prolonged up to 6 sec
Switch Voltage	2-16 VDC
Switch Current	0.15A
Switch Resistance OFF	> 20M Ohm
Switch Resistance ON	< 10 Ohm
Switch On Duration	Up to 6 sec
Contact Configuration	Free Polarity

---

## Mechanical Data

---

Housing Materials	Aluminum 6061 T651, Stainless Steel (Type 303, 304 or 316) or Plastic
Actuating Force	2-5 Newtons
Connection	22 AWG standard, free leads

---

## Environmental Data


---

Operating Temperature	-20°C to +75°C
Storage Temperature	-40°C to +85°C
IP Protection	IP69 K

---


## Electrical Diagram

---



## Technical Drawing

---



\*The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Users should evaluate the suitability and test each product selected for their own applications.